


	B 125	Z 250	C 285 N	C 320 N	C 350	C 400	C 450	C 500	C 550	C 600	
Weight, excluding hammer	kg	485	980	1320	1370	2500	2550	2600	2655	2700	2750
Maximum reach (M)	m	2.0	3.9	4.7	4.9	5.4	5.8	6.3	7.0	7.3	7.7
Horizontal reach (H)	m	1.2	2.7	3.2	3.5	3.9	4.3	4.6	5.6	5.8	6.2
Vertical reach (V)	m	1.1	0.9	3.3	3.7	4.2	4.6	4.9	5.0	5.1	5.6
Swing	°	95	360	170	170	170	170	170	170	170	170
Recommended hammer types		S 21	S 22-S 25	S 23-S 27	S 23-S 27	S 25-E 64	S 25-E 64	S 25-E 64	S 25-S 29	S 25-S 29	S 25-S 29



	D 300	D 425	S 550	S 630	M 550	M 630	XM 500/HD	XM 600/HD	
Weight, excluding hammer	kg	1630	1870	4250	4400	6400	6700	6450/7250	6650/7400
Maximum reach (M)	m	4.6	6.9	7.8	8.9	7.9	8.9	7.7/8.0	8.7/9.0
Horizontal reach (H)	m	2.9	4.2	5.9	6.5	5.9	6.6	5.6/5.5	6.5/6.4
Vertical reach (V)	m	2.6	3.8	4.9	5.8	5.0	5.8	4.8/5.1	5.8/6.1
Swing	°	360	360	170	170	170	170	170	170
Recommended hammer types		S 23-27	S 23-27	S 27-E 66	S 27-E 66	E 65-E 68	E 65-E 68	E 63-E 68/E 65-G 80	E 63-E 68/E 65-G 80



	XM 750/HD	XM 700	XM 850	XM 950	L 850	L 940	XL 940	XL 1200	
Weight, excluding hammer	kg	6850/7800	7350	7750	7950	7700	7900	15100	16500
Maximum reach (M)	m	10.1/10.4	9.7	11.0	11.7	10.6	12.0	12.0	14.5
Horizontal reach (H)	m	8.0/7.9	7.4	8.9	9.8	8.3	9.2	9.8	12.2
Vertical reach (V)	m	6.5/6.8	6.8	7.5	8.5	6.9	7.8	9.2	10.6
Swing	°	170	170	170	170	170/360	170/360	170/360	170/360
Recommended hammer types		E 63-E 68/E 65-G 80	E 63-E 68	E 63-E 68	E 63-E 64	E 65-E 68	E 65-E 68	E 68-G 90	E 65-E 68