

RAMMER HYDRAULIC HAMMERS



Compact range

Model	Working weight, kg (lb)	Impact rate, bpm	Operating pressure, bar (psi)	Tool diameter, mm (in)	Acceptable oil flow, l/min (gal/min)	Mini excavator weight, allowed range, t (lb)
108	75-85 (170-190)	400-1900	100-140 (1450-2030)	104 (4.09)	12-30 (3.2-7.9)	0.8-1.8 (1800-4000)
211	105-120 (230-260)	400-1900	100-140 (1450-2030)	119 (4.69)	14-40 (3.7-10.6)	1.2-2.6 (2600-5700)
315	145-160 (320-350)	400-1900	100-140 (1450-2030)	131 (5.16)	16-50 (4.2-13.2)	1.6-3.6 (3500-7900)
522	220-245 (490-540)	400-1900	110-150 (1595-2175)	150 (5.91)	20-70 (5.3-18.5)	2.5-5.5 (5500-12100)



Small range

Model	Working weight, kg (lb)	Impact rate, bpm	Operating pressure, bar (psi)	Tool diameter, mm (in)	Acceptable oil flow, l/min (gal/min)	Carrier weight, allowed range, t (lb)
155	90 (200)	1000-2600	80-130 (1160-1885)	36 (1.42)	15-33 (4.0-8.7)	0.6-1.8 (1300-4000)
255	110 (240)	600-3200	95-150 (1380-2175)	40 (1.57)	15-35 (4.0-9.2)	0.8-2.5 (1800-5500)
355	150 (330)	800-3000	90-150 (1305-2175)	48 (1.89)	25-55 (6.6-14.5)	1.1-3.6 (2400-7900)
455	230 (510)	700-2600	100-170 (1450-2465)	56 (2.20)	40-70 (10.6-18.5)	2.7-5.2 (6000-11500)
555	275 (610)	600-1800	90-140 (1305-2030)	72 (2.83)	35-90 (9.2-23.8)	3.2-8.0 (7100-17600)
777	385 (850)	500-1700	90-140 (1305-2030)	80 (3.15)	40-120 (10.6-31.7)	4.3-9.5 (9500-20900)
999	505 (1110)	500-1700	100-140 (1450-2030)	90 (3.54)	50-150 (13.2-39.6)	5.8-13.0 (12800-28700)
1322	850 (1870)	500-1000	125-150 (1815-2175)	95 (3.74)	60-120 (15.9-31.7)	9-15 (19800-33100)