



Medium range

Model	Working weight, kg (lb)	Impact rate, bpm	Operating pressure, bar (psi)	Tool diameter, mm (in)	Acceptable oil flow, l/min (gal/min)	Carrier weight, allowed range, t (lb)
1533	870 (1920)	550-1050	140-160 (2030-2320)	105 (4.13)	80-140 (21.1-37.0)	10-19 (22000-41900)
1655	1080 (2380)	540-920	135-145 (1960-2105)	115 (4.53)	90-130 (23.8-34.3)	12-20 (26500-44100)
2155	1240 (2730)	490-780	140-160 (2030-2320)	118 (4.65)	120-180 (31.7-47.6)	16-26 (35300-57300)
2166	1400 (3090)	430-790	140-160 (2030-2320)	125 (4.92)	120-180 (31.7-47.6)	18-26 (39700-57300)
2577	1760 (3880)	450-750	135-145 (1960-2105)	135 (5.31)	140-200 (37.0-52.8)	21-30 (46300-66100)



Large range

Model	Working weight, kg (lb)	Impact rate, bpm, Long/Short stroke	Operating pressure, bar (psi)	Tool diameter, mm (in)	Acceptable oil flow, l/min (gal/min)	Carrier weight, allowed range, t (lb)
3288	2400-2500 (5290-5510)	370-630/460-740	150-160 (2175-2320)	142 (5.59)	160-250 (42.3-66.0)	26-40 (57300-88200)
4099	3380-3540 (7450-7800)	400-560/520-700	150-160 (2175-2320)	166 (6.54)	250-350 (66.0-92.5)	34-55 (75000-121300)
5011	4750-5200 (10470-11460)	370-530	160-170 (2320-2460)	190 (7.48)	280-380 (73.9-100.4)	43-80 (94800-176400)
7013	7000 (15432)	350-450	150-170 (2175-2465)	203 (7.99)	300-400 (79.3-105.7)	60-100 (132300-220500)

RAMMER BOOMS

